



1689.00 EUR  
incl. 19% VAT, plus [shipping](#)

- 1366x768 Multi-Touchscreen !
- Fanless ! IP65 Front !
- Intel Kaby Lake CPU !
- 2x LAN, 2x COM !



Support:  [Specifications](#)

D151 series is a 15.6" ultra-thin wide-screen fanless Panel PC featuring Intel Kaby Lake ULV Core-i CPU. The distinct aluminum extrusion frame with matte black or silver finish gives the system an understated luxury and elegant look. The series also featuring a bright TFT-LCD with LED backlight display and true flat 10-point projective capacitive multi-touch front panel that's IP65 compliant, along with optional universal snap-in peripherals (MSR, Smart card reader, NFC/ RFID reader, barcode scanner, camera), making it perfect for diversified self-service and interactive signage markets including retail, hospitality, gaming, corporate, healthcare and light

industrial applications.

|                                     |   |
|-------------------------------------|---|
| Model Name                          | D151-11KS   |
| Motherboard                         | PD11KS  |
| Processor                           | Intel Kaby Lake-U i3-7100U with integrated graphics (Compatible with Skylake 3955U / i3-6100U / i5-6300U / i7-6600U and KabyLake 3965U / i5-7300U / i7-7600U) |
| System Memory                       | 2 x DDR4 SO-DIMM, support up to 32GB  |
| Processor Graphic                   | Intel® HD Graphics 620 (Graphics Burst Frequency 1.10GHz)   |
| Touch Display                       |   |
| LCD Size                            | 15.6" TFT LCD with LED Backlight 50000 lifetime   |
| Brightness                          | 500nits   |
| Resolution                          | 1366 x 768  |
| Viewing Angle                       | 170°/160°   |
| Touch Screen                        | True-flat 10 points projective capacitive touch   |
| Storage                             |   |
| HDD/SSD                             | 1 x 2.5 internal HDD/SSD bay  |
| Expansion                           |   |
| Extension slots                     | M.2 (2230) : 1 x M.2 E key for wireless network<br>MiniPCIe : 1 x full length mPCIe supporting mSATA  |
| I/O Ports                           |   |
| DC Jack                             | 1 (8V to 24V wide-range voltage input)  |
| USB3.0                              | 4   |
| GigaLAN (10/100/1000)               | 2   |
| Display-Port (support 4K 3840x2160) | 1   |
| Audio jack                          | 1 x combo jack w/mic-in and line-out  |
| HDMI-out                            | 1   |
| Serial Port                         | 1 x RS-232, 1 x RS-232/422/485  |
| Thermal Solution                    |   |
| Thermal Solution                    | Fanless   |
| Audio                               |   |
| Stereo Speaker                      | 2W x 2  |
| Power                               |   |
| Power Supply                        | 65W/19V   |
| Certification                       |   |
| EMC & Safety                        | CE/FCC Class A  |
| Environment                         |   |
| Operating Temperature               | 0°C ~ 40°C (32°F~104°F)   |
| Storage Temperature                 | -20°C ~ 60°C(-4°F~140°F)  |
| Relative Humidity                   | 10%~95% @40°C non-condensing  |
| Front Panel Protection              | IP65 Compliant  |
| Dimension                           | 400 x 250 x 44 (mm)   |
| Weight                              | 4.8kg (10.58 lb)  |
| Mounting                            | 100mm x 100mm VESA  |
| Operating System                    | win10, linux support by request   |